

Endurance FR50 Underlay

Applications:	Felt is recommended for Axminster and Wilton carpet where the seams bed in to the felt giving an excellent finish. The FR range is widely used in areas of high traffic such as pubs, nightclubs and hotels. It gives an unmatched mix of value and wear for our contract customers.
----------------------	--



Automotive Felt



Carpet Underlay




Geo Textile Felt



Horticultural Felt



Specialist Felt



Engineering

www.angloreycling.com—innovating with recycled fibre

Fibre Composition:	Hair/Jute/Mixed fibres (100% Recycled)
Nominal Weight:	1695g/m ² (+/- 5%) (50oz/yd ²)
Nominal Thickness:	11.0mm (+/- 0.5mm)
Roll Width:	1.37m
Roll Length:	12.5m/11.0m
Standard Roll Area:	17.125m ² /15.07m ²
Flame Retardancy: <i>BS4790:1987</i> <i>(Hot Metal Nut Test)</i>	Endurance FR achieves a 'low radius of effects of ignition' – no more than 20 mm against maximum permitted of 35 mm for low radius classification.
Static Loading: <i>BS4939</i>	Thickness loss after 24 hours loading and 24 hours recovery: Retained FR50 56%
Sound Impact: <i>BS2750 Part 8:1980</i>	Weighted impact sound improvement 24dB
Thermal Resistance: <i>BS4745</i>	2.6 Togs indicative
Other Information:	All products held to stock.



Anglo Recycling Technology Ltd

Tong Lane, Whitworth

Rochdale, Lancs OL12 8BG

Tel: +44 (0)1706 853513 Fax: +44 (0)1706 853625

E-mail: info@angloreycling.com

Web: www.angloreycling.com